



SPECIFICATIONS  
 Rated Current:1.0AMP  
 Contact Resistance:20mΩMax  
 Withstand Voltage:500V AC/DC  
 Insulation Resistance:1000MΩMin  
 Operation Temperature:-40°C to +105°C

Contact Material:Brass  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Standard: PA6T  
 Max.Processing Temp: 230°C for 30-60 seconds  
 (260°C for 10 seconds)

Dimension antitheses list				
ITEM	PA	PB	W	L
Standard	4.00	1.50	4.20	5.50

**Ordering Information**

PZ 127 - \* - N - \* - \* - \*\* - \*

No.of Rows 1=Single Row 2=Dual Row 3=Triple Row 4=Quadruple Row	No.of Pins 2=50Pin	Type 2=直插 S=贴片 M=穿板 R=反型	Length (mm)	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin	1=TYPE 1 2=TYPE 2
---	-----------------------	--------------------------------------	----------------	--	----------------------

			GENERAL TOLERANCE		制 图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM	TOL	审 核 CHECK					
			X.X	±0.30	批 准 APPROVAL		产品名称 TITLE	1.27 单排 排针 贴片	版本 REV.	A
1			初版发行		比 例 SCALE		产品料号 PART NO.	PZ127-1-N-S-1.0-XX-X (L5.5)	单 位 UNITS	mm
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle ±3.0°		投 影 Projection			材 料 MATERIAL	页 次 SHEET	1/1