



SPECIFICATIONS
 Rated Current:1.5AMP
 Contact Resistance:20mΩMax
 Withstand Voltage:500V AC/DC
 Insulation Resistance:1000MΩMin
 Operation Temperature:-40°c to +105°c

Contact Material:Brass
 Contact Plating:Au or Sn Over Ni
 Insulator Material:Polyester(UL94V-0)
 Standard: PA6T
 Max.Processing Temp: 230°C for 30-60 seconds
 (260°C for 5-10 seconds)

Pitch	H (mm)
2.00mm	2.0
	2.2
	2.8
	4.0
	4.3
	4.6
	6.35
	7.2
	9.35

Ordering Information

PM 200 - * - N - * - * - ** - *

No. of Rows
1=Single Row
2=Dual Row

No. of Pins
2-40Pin

Type
2=排针
4=排针
5=空脚
6=空脚

Length (mm)

Contact Plating
G0:Gold Flash
G1:1u" Gold
G2:3u" Gold
G3:5u" Gold
G4:10u" Gold
G5:15u" Gold
G6:30u" Gold
S0:Gold Flash/Tin
S1:Tin

1=TYPE 1
2=TYPE 2

GENERAL TOLERANCE			制图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
DIM	TOL		审核		产品名称	2.00 单排 排母 贴片	版本	A
X.X	±0.30		检查		TITLE	塑高6.35	REV.	
			批准		产品料号	PM200-1-N-S-6.35-XX-X(L6.95)	单位	mm
1	初版发行		APPROVAL		PART NO.		UNITS	
序号	变更内容	日期	SCALE		材料		页次	1/1
No.	MODIFY CONTENT	MODIFY DATE	Angle	±3.0°	投影		SHEET	