



**SPECIFICATIONS**

Rated Current:1.0AMP  
 Contact Resistance:20mΩ Max  
 Withstand Voltage:500V AC/DC  
 Insulation Resistance:1000MΩ Min  
 Operation Temperature:-40°c to +105°c

Contact Material:Brass  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Standard: PA6T  
 Max.Processing Temp: 230°C for 30-60 seconds  
 (260°C for 10 seconds)

Dimension antitheses list

ITEM	PA	A	PC	L
Standard	4.00	2.50	5.50	12.00
Alternate				

**Ordering Information**

PZ 127 - \* - N - WS - \* - \*\*

No.of Rows  
 1=Single Row  
 2=Dual Row

No.of Pins  
 2-50Pin

Type  
 Z=直插  
 W=弯插  
 S=立贴  
 M=带脚

Length (mm)

Contact Plating  
 C0:Gold Flash  
 G1:1u" Gold  
 G2:3u" Gold  
 G3:5u" Gold  
 G4:10u" Gold  
 G5:15u" Gold  
 G6:30u" Gold  
 S0:Gold Flash/Tin  
 S1:Tin

			GENERAL TOLERANCE		制 图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
			DIM	TOL	审 核 CHECK		产品名称 TITLE	1.27双排 排针 卧贴 (塑高2.5)	版本 REV.	A
			X.X	±0.30	批 准 APPROVAL		产品料号 PART NO.	PZ127-2-N-WS-2.5-XX(L12.0)	单 位 UNITS	mm
1	初版发行		X.XXX	±0.10	比 例 SCALE		材 料 MATERIAL		页 次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°	投 影 Projection					