



SPECIFICATIONS
 Rated Current:1.5AMP
 Contact Resistance:20mΩ Max
 Withstand Voltage:500V AC/DC
 Insulation Resistance:1000MΩ Min
 Operation Temperature:-40°c to +105°c

Contact Material:Brass
 Contact Plating:Au or Sn Over Ni
 Insulator Material:Polyester(UL94V-0)
 Standard: PA6T
 Max.Processing Temp: 230°C for 30-60 seconds
 (260°C for 10 seconds)

Pitch	H (mm)
2.00mm	1.0
	1.5
	2.0
	2.5
	3.0
	4.0

Dimension antitheses list				
ITEM	PA	PB	W	L
Standard	3.80	2.50	4.50	6.30

Ordering Information

PZ 200 - * - N - * - * - ** - *

No.of Rows
 1=Single Row
 2=Dual Row
 3=Triple Row
 4=Quadruple Row

No.of Pins
 2=40Pin
 3=60Pin
 4=80Pin

Type
 2=Type 1
 3=Type 2

Length (mm)
 G0:Gold
 G1:1u" Gold
 G2:2u" Gold
 G3:5u" Gold
 G4:10u" Gold
 G5:15u" Gold
 G6:30u" Gold
 S0:Gold Flash/Tin
 S1:Tin

Contact Plating
 1=TYPE 1
 2=TYPE 2

GENERAL TOLERANCE		制图 DRAWING
DIM	TOL	审核 CHECK
X.X	±0.30	批准 APPROVAL
X.XX	±0.20	比例 SCALE
X.XXX	±0.10	投影 Projection
Angle	±3.0°	

深圳市华灿天禄电子有限公司
 ShenzhenhuacantianluELECTRONICS CO.,LTD

产品名称 TITLE	2.00 单排 排针 贴片 塑高2.0	版本 REV.	A
产品料号 PART NO.	PZ200-1-N-S-2.0-XX-XX (L6.3)	单位 UNITS	mm
材料 MATERIAL		页次 SHEET	1/1

序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE
1	初版发行	