



SPECIFICATIONS
 Rated Current:5.0AMP
 Contact Resistance:20mΩ Max
 Withstand Voltage:500V AC/DC
 Insulation Resistance:1000MΩ Min
 Operation Temperature:-40°c to +105°c

Contact Material:Brass
 Contact Plating:Sn Over Ni
 Insulator Material:Polyester(UL94V-0)
 Standard: LCP
 Max.Processing Temp: 230°C for 30-60 seconds
 (260°C for 5 seconds)

Dimension antitheses list				
ITEM	PA	PB	W	L
Standard	8.00	6.50	10.00	14.50
Alternate				

Ordering Information

PZ 396 - * - N - S - * - ** - *

No. of Rows 1=Single Row 2=Dual Row	No. of Pins 2=20Pin	Type N=单排 S=双排 S=双排 S=双排	Length (产品长度)	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin	1=TYPE 1 2=TYPE 2
---	------------------------	--------------------------------------	------------------	--	----------------------

			GENERAL TOLERANCE		制 图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
			DIM	TOL	审 核 CHECK		产品名称 TITLE	3.96单排 排针 贴片(塑高3.2)	版本 REV.	A
			X. X	±0.30	批 准 APPROVAL		产品料号 PART NO.	PZ396-1-N-S-3.2-XX-X(L14.5)	单 位 UNITS	mm
1	初版发行		X. XX	±0.20	比 例 SCALE		材 料		页 次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°	投 影 Projection					