



SPECIFICATIONS
 Rated Current:3.0AMP
 Contact Resistance:20mΩMax
 Withstand Voltage:1000V AC/DC
 Insulation Resistance:1000MΩMin
 Operation Temperature:-40°c to +105°c

Contact Material:Brass
 Contact Plating:Au Over Ni
 Insulator Material:Polyester(UL94V-0)
 Standard: PA6T
 Soldering Temperature:260°C±5° 5S

Dimension antitheses list				
ITEM	PA	PB	W	L
Standard	6.00	3.20	4.80	9.20
Alternate				

Ordering Information

PZ 254 - * - N - S - * - ** - *

No. of Rows 1=Single Row 2=Dual Row	No. of Pins 2=40Pin	Type 2=有针 S=无针 P=带脚	Length (产品长度)	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin	1=TYPE 1 2=TYPE 2
---	------------------------	------------------------------	------------------	--	----------------------

			GENERAL TOLERANCE		制 图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
			DIM	TOL	审 核 CHECK					
			X. X	±0.30	批 准 APPROVAL		产品名称 TITLE	2.54单排 排针 贴片(塑高2.5)	版本 REV.	A
			X. XX	±0.20	比 例 SCALE		产品料号 PART NO.	PZ254-1-N-S-2.5-XX-X (L9.2)	单 位 UNITS	mm
			X. XXX	±0.10	投 影 Projection		材 料 MATERIAL		页 次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°						