



SPECIFICATIONS
 Rated Current:5.0AMP
 Contact Resistance:20mΩ Max
 Withstand Voltage:1000V AC/DC
 Insulation Resistance:1000MΩ Min
 Operation Temperature:-40°c to +105°c

Contact Material:Brass
 Contact Plating:Au or Sn Over Ni
 Insulator Material:Polyester(UL94V-0)
 Standard: LCP
 Max.Processing Temp: 230°C for 30-60 seconds
 (260°C for 5 seconds)

Dimension antitheses list			
ITEM	PA	PC	L
Standard	8.00	3.50	14.00

Ordering Information

PZ 508 - * - N - Z - * - **

No.of Rows 1=Single Row 2=Dual Row	No.of Pins 2-40Pin	Type Z=直针 W=弯针 S=立轴 R=穿轴	Length (mm)	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin
--	-----------------------	--------------------------------------	----------------	--

Recommended P.C.B Layout(Top Side)
 (PCB BOARD TOLERANCE±0.05)

GENERAL TOLERANCE		制图 DRAWING	
DIM	TOL	审核 CHECK	批 准 APPROVAL
X.X	±0.30		
X.XX	±0.20		
X.XXX	±0.10		
Angle	±3.0°	投影 Projection	

深圳市华灿天禄电子有限公司
 ShenzhenhuacantianluELECTRONICS CO.,LTD

1	初版发行		产品名称 TITLE	5.08单排 排针 直针(塑高2.5)	版本 REV.	A
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	产品料号 PART NO.	PZ508-1-N-Z-2.5-XX(L14.0)	单位 UNITS	mm
			材料 MATERIAL		页次 SHEET	1/1