



SPECIFICATIONS  
 Rated Current:3.0AMP  
 Contact Resistance:20mΩ Max  
 Withstand Voltage:1000V AC/DC  
 Insulation Resistance:1000MΩ Min  
 Operation Temperature:-40°C to +105°C

Contact Material:Copper Alloy  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Standard: PA6T  
 Max.Processing Temp: 260°C±5°C 5S

**Ordering Information**

PM 254 - \* - N - WS - \* - \*\*

No. of Rows 1=Single Row 2=Dual Row	No. of Pins 2-40Pin	Type Z=直插 S=贴片 W=弯插	Length (Plastic) (mm)	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin
---	------------------------	------------------------------	--------------------------	--

			GENERAL TOLERANCE		制 图 DRAWING		<b>深圳市华灿天禄电子有限公司</b> ShenzhenhuacantianluELECTRONICS CO., LTD				
			DIM	TOL	审 核 CHECK						
			X. X	±0.30	批 准 APPROVAL		产品名称 TITLE		2.54双排 排母 卧贴(塑高8.5)		
			X. XX	±0.20	比 例 SCALE		产品料号 PART NO.		PM254-2-N-WS-8.5-XX(L16.9)		
			X. XXX	±0.10	投 影 Projection		材 料 MATERIAL				
			Angle	±3.0°			单 位 UNITS		mm		
1	初版发行	日期								版 本 REV.	A
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE								单 位 UNITS	mm
										页 次 SHEET	1/1