



SPECIFICATIONS  
 Rated Current:3.0AMP  
 Contact Resistance:20mΩMax  
 Withstand Voltage:1000V AC/DC  
 Insulation Resistance:1000MΩMin  
 Operation Temperature:-40°C to +105°C

Contact Material:Brass  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Resistance To Soldering Heat:  
 245°C±5°C, 10s(PBT insulator)  
 260°C±5°C, 10s(PA6T insulator)

**Ordering Information**

HC-NJ 254 - \* - N - \* - \* - \* - \*

No. of Rows 2= Dual Row	No. of Pins 6-64Pin	Type (01.0) (02.0) (03.0)	Length (mm) (01.0) (02.0)	Contact Plating Flash	Color B=Black G=Grey	Latch Type L=Long Latch S=Short Latch N= Without Latch
				00=Gold		
				01=1u" Gold		
				02=2u" Gold		
				03=3u" Gold		
				04=10u" Gold		
				05=15u" Gold		
				06=30u" Gold		
				08=Gold Flash/Tin		
				11=Tin		

			GENREL TOLERANCE		制图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD				
			DIM	TOL	审核 CHECK		产品名称 TITLE		2.54 牛角 直针	版本 REV.	A
			X.X	±0.30	批准 APPROVAL		产品料号 PART NO.		HC-NJ254-2-N-Z-27.8-XX-X-L	单位 UNITS	mm
1			初版发行				材料			页次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°	投影 Projection						