



MECHANICAL:

1. HOUSING MATERIAL:PA46 PA66 PBT BLACK
2. INSERT MATERIAL:PA46 PA66 PBT BLACK
3. TERMINAL:PHOSPHOR BRONZE $\phi 0.46\text{MM}$. G/FU" GOLD PLATING
4. SHIELD:BRASS T=0.2mm PLATED NICKEL 30u" Min
5. OPERATING LIFE:750 CYCLES MIN
6. MATING/UNMATING FORCE:30N/3.06KGf MAX
1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5 AMP
3. CONTACT RESISTANCE:30m MAX
4. INSULATION RESISTANCE:500 MEGA OHMS MIN. INITIAL
5. DIELECTRIC STRENGTH:1000VAC RMS 50HZ OR 60HZ, 1MIN
1. STORAGE:-40°C TO +85°C
2. OPERATION:-40°C TO +85°C
3. The mark with "*" is key inspection dimension for QC

			GENERAL TOLERANCE	制图 DRAWING	04			
			DIM TOL	审核 CHECK				
			X.X ±0.30	批准 APPROVAL	产品名称 TITLE	网络插座	版本 REV.	A
			X.XX ±0.20	比例 SCALE	产品料号 PART NO.	HC-RJ45-059A-2x1-7	单位 UNITS	mm
			X.XXX ±0.10	投影 Projection	材料 MATERIAL		页次 SHEET	1/1
1	初版发行		Angle ±3.0°					
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE						

深圳市华灿天禄电子有限公司
 ShenzhenhuacantianluELECTRONICS CO., LTD