



**MATERIAL:**  
 HOUSING:PA46,PBT,BLACK.  
 TERMINAL: PHOSPHOR BRONZE Ø0.46MM  
 6/FU'GOLD PLATING  
 SHIELD:C2680,T=0.20MM, 20 MIN NICKEL 'PLATING  
 NO ALL AREA

**MACHANICAL:**  
 DURABILITY: 750 CYCLES MIN,12.5MM/MINUTE.  
 INSERTION FORCE: 2.2KG.F MAX.  
 RETENTION STRENGTH: 7.7KG.F BETWEEN JACK AND PLUG.  
 OPERATING TEMPERATURE: -40℃~+85℃.  
 STORAGE TEMPERATURE: -40℃~+85℃.  
 ALL CRITICAL DIMENSIONS WITH "ø"

VOLTAGE: 125 VOLTS AC.  
 CURRENT RATING: 1.5AMP.  
 DIELECTRIC STRENGTH: 1000 VAC RMS 50HZ OR 60HZ,1MIN.  
 INSULATION RESISTANCE: 500 MEGA OHMS MIN. INITIAL  
 AFTER 500V DC FOR 1 MINUTE.  
 CONTACT RESISTANCE: SINGLE TERMINAL 30 MILLIOHMS MAX.  
 INITIAL 50 MILLIOHMS MAX. AFTER  
 DURABILITY TEST.

**LED Specification**

Standard LED Color	LED Wavelength	Foward(A)	Foward(V)
Green	568nm	20mA	1.85-2.45V
Yellow	585nm	20mA	1.7-2.2V



			GENREL TOLERANCE	制图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
			DIM TOL	审核 CHECK				
			X.X ±0.30	批准 APPROVAL	产品名称 TITLE	网络插座	版本 REV.	A
			X.XX ±0.20	比例 SCALE	产品料号 PART NO.	HC-RJ45-5224-4-2-H-04	单位 UNITS	mm
			X.XXX ±0.10	投影 Projection	材料 MATERIAL		页次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle ±3.0°					