



Electrical

Current rating: 1.5 AMPS

Voltage rating: 125V AC

Insulation resistance: $\geq 500\text{m}\Omega$

Withstanding voltage: AC 1000V MS
50HZ 或 60Hz Min

Contact rating: $\leq 30\text{m}\Omega$

Working temperature: $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$

机构特性:

1. 塑壳材质: PBT、PA46、PA66黑色
2. 圆针材质: 磷青铜, $\text{Ø}0.46\text{mm}$
3. 圆针电镀: 镍底, 表面全部镀金
4. 外壳材质: 黄铜, 厚度0.2, 镀镍
5. 可靠性: 最少750次插拔
6. 插入力: 30N
7. 相对湿度: $< 80\%$

			GENERAL TOLERANCE	制图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD				
			DIM TOL	审核 CHECK	产品名称 TITLE		网络插座 (无灯无弹)	版本 REV.	A
			X.X ± 0.30	批准 APPROVAL	产品料号 PART NO.		HC-RJ45-059-2-4	单位 UNITS	mm
			X.XX ± 0.20	比例 SCALE	材料 MATERIAL			页次 SHEET	1/1
			X.XXX ± 0.10	投影 Projection					
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle $\pm 3.0^{\circ}$						