



NOTES:

备注

1. Copper, Bright tin plated
黄铜, 镀亮镍
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 45A
额定电流: 45A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/Pin	Product No.	Material
Pin (插脚)	0.8±0.05mm	M4 (螺牙)	2个	1620#16x20mm	Pin	产品序号	Copper (铜)
Nut (螺母)	1.0±0.05mm	M4 (螺牙)	2个	Pin		Copper (铜)
Gasket (垫片)	2.0±0.05mm	M4 (螺牙)	2个				Copper (铜)
	3.0±0.05mm		2个				Copper (铜)

		GENREL TOLERANCE		制图	07			深圳市华灿天禄电子有限公司 ShenzhenhuacantianlueELECTRONICS CO.,LTD		
		DIM	TOL	审核				产品名称 TITLE PCB 焊接端子 厚度0.8 插板 铆垫片 M4 4焊脚 8x8x8.7mm		
		5 or more	±0.35	批准				版本号 REV. A		
		2~5	±0.25	比例				产品料号 PART NO. HC-RG0844-0808-D201-07		
		0~2	±0.15	投影				单位 UNITS mm		
序号	变更内容	日期		投影				材料 MATERIAL 页次 SHEET 1/1		
No.	MODIFY CONTENT	MODIFY DATE								