



NOTES:

- 备注
- 1.Brass or purple copper,Bright tin-plating
黄铜或者紫铜, 镀亮锡
 - 2.Wire screw hole M5
压线螺孔M5
 - 3.Current Rating: 80A
额定电流:80A
 - 4.There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 - 5.Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * * * * - * * * * - * * * * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Product No.	Material
①插片 (插片)	①1.5mm (1.5mm)	①M5 (M5)	①12x17.5mm (12x17.5mm)	①12x17.5mm (12x17.5mm)	①12x17.5mm (12x17.5mm)	①紫铜 (紫铜)
②螺母 (螺母)	②1.5mm (1.5mm)	②M5 (M5)	②12x17.5mm (12x17.5mm)	②12x17.5mm (12x17.5mm)	②12x17.5mm (12x17.5mm)	②紫铜 (紫铜)
③螺母 (螺母)	③1.5mm (1.5mm)	③M5 (M5)	③12x17.5mm (12x17.5mm)	③12x17.5mm (12x17.5mm)	③12x17.5mm (12x17.5mm)	③紫铜 (紫铜)
④螺母 (螺母)	④1.5mm (1.5mm)	④M5 (M5)	④12x17.5mm (12x17.5mm)	④12x17.5mm (12x17.5mm)	④12x17.5mm (12x17.5mm)	④紫铜 (紫铜)

		GENREL TOLERANCE		制图	07		
		DIM	TOL	审核			
		5 or more	±0.35	CHECK			
		2~5	±0.25	批准	产品名称	PCB 焊接端子 厚度1.5 插板 铆垫片	版本
		0~2	±0.15	APPROVAL	TITLE	M5 4焊脚 12x12x17.5mm	REV.
		Angle	±3.0°	比例	产品料号	HC-RG1554-1212-D705-07	单位
序号	变更内容	日期		SCALE	PART NO.		mm
No.	MODIFY CONTENT	MODIFY DATE		投影	MATERIAL		页次
							SHEET
							1/1

深圳市华灿天禄电子有限公司
ShenzhenhuacantianlueELECTRONICS CO., LTD