



NOTES:

- 备注
1. Brass or purple copper, Bright tin-plating  
黄铜或紫铜，镀亮锡
  2. Wire screw hole M4  
压线螺孔M4
  3. Current Rating: 70A  
额定电流:70A
  4. There shall be no defects such as pin deformation and burrs.  
不得有脚变形，毛刺等缺陷
  5. Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

Ordering Information

HC - \* \*\* \* - \*\*\*\* - \* \*\* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/P SERT	Product No.	Material
Pin	0.8~1.0mm	M3 (螺牙)	2个	1620=16x20mm	Pin		紫铜
Teeth	1.0~1.2mm	M4 (螺牙)	2个	.....	Dip		黄铜
Nut	1.5~1.8mm	M4 (螺牙)	2个				紫铜
Gasket	2.0~2.5mm	M4 (螺牙)	2个				黄铜
	2.5~3.0mm	M4 (螺牙)	2个				紫铜
	3.0~3.5mm	M4 (螺牙)	2个				黄铜

			GENERAL TOLERANCE	制图	07	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM TOL	审核		产品名称	PCB 焊接端子 厚度1.2 插板 铆垫片	版本	A
			5 or more ±0.35	CHECK		TITLE	M4 4焊脚 9x9x15.5mm	REV.	
			2~5 ±0.25	批准		产品料号	HC-RG1244-0909-D505-07	单位	mm
			0~2 ±0.15	APPROVAL		PART NO.		页次	1/1
序号	变更内容	日期	Angle ±3.0°	投影		MATERIAL		SHEET	
No.	MODIFY CONTENT	MODIFY DATE							