



NOTES:

- 备注
1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
 2. Wire screw hole M4
压线螺孔M4
 3. Current Rating: 70A
额定电流: 70A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/P	Product No.	Material
Pin (插脚)	0.8±0.05mm	0.8±0.05 (螺牙)	0.8±0.05 (焊脚)	1620#16x20mm	Pin	产品序号	镀锡铜 (黄铜)
Pin Nut (插脚螺母)	1.0±0.1mm	1.0±0.1 (螺牙)	1.0±0.1 (焊脚)	Pin	镀锡铜 (黄铜)
Pin Gasket (插脚垫片)	1.5±0.1mm	1.5±0.1 (螺牙)	1.5±0.1 (焊脚)	Pin	镀锡铜 (黄铜)
	2.0±0.2mm	2.0±0.2 (螺牙)	2.0±0.2 (焊脚)	Pin	镀锡铜 (黄铜)
	2.5±0.2mm	2.5±0.2 (螺牙)	2.5±0.2 (焊脚)	Pin	镀锡铜 (黄铜)
	3.0±0.2mm	3.0±0.2 (螺牙)	3.0±0.2 (焊脚)	Pin	镀锡铜 (黄铜)

			GENERAL TOLERANCE	制图	07			深圳市华灿天禄电子有限公司 ShenzhenhuacuantianluELECTRONICS CO., LTD		
			DIM TOL	审核				产品名称 TITLE PCB 焊接端子 厚度1.2 插板 铆垫片 M4 4焊脚 12x9x15.5mm		
			5 or more ±0.35	批准				版本号 REV. A		
			2~5 ±0.25	比例				产品料号 PART NO. HC-RG1244-1209-D515-07		
			0~2 ±0.15	投影				单位 UNITS mm		
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle ±3.0°	投影 Projection	材料 MATERIAL			页次 SHEET 1/1		