



NOTES:

- 备注
- 1.Brass or purple copper,Bright tin-plating
黄铜或者紫铜, 镀亮锡
 - 2.Wire screw hole M5
压线螺孔M5
 - 3.Current Rating: 80A
额定电流:80A
 - 4.There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 - 5.Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * * * * - * * * * - * * * * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Product No.	Material
插板 (插脚)	0.4mm	M5 (螺牙)	1.5 (焊脚)	100#M6x20mm	PCB焊脚	黄铜 (黄铜)
螺母 (螺母)	0.4mm	M5 (螺牙)	1.5 (焊脚)	100#M6x20mm	PCB焊脚	紫铜 (紫铜)
螺柱 (螺柱)	0.4mm	M5 (螺牙)	1.5 (焊脚)	100#M6x20mm	PCB焊脚	紫铜 (紫铜)
螺帽 (螺帽)	0.4mm	M5 (螺牙)	1.5 (焊脚)	100#M6x20mm	PCB焊脚	紫铜 (紫铜)
螺柱 (螺柱)	0.4mm	M5 (螺牙)	1.5 (焊脚)	100#M6x20mm	PCB焊脚	紫铜 (紫铜)
螺帽 (螺帽)	0.4mm	M5 (螺牙)	1.5 (焊脚)	100#M6x20mm	PCB焊脚	紫铜 (紫铜)

		GENEAL TOLERANCE		制图	07		
		DIM	TOL	审核			
		5 or more	±0.35	批准			
		2~5	±0.25	比例			
		0~2	±0.15	SCALE			
		Angle	±3.0°	投影			
1	初版发行	日期					
序号	变更内容	MODIFY DATE	MODIFY CONTENT				
				深圳市华灿天禄电子有限公司 ShenzhenhuacantianlueELECTRONICS CO., LTD			
		产品名称	PCB 焊接端子 厚度1.5 插板 铆垫片	版本	A		
		TITLE	M5 4焊脚 12x12x13.5mm	REV.			
		产品料号	HC-RG1554-1212-D703-07	单位	mm		
		PART NO.		UNIT			
		材料		页次	1/1		
		MATERIAL		SHEET			