



NOTES:  
备注

1. Brass or purple copper, Bright tin-plating  
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4  
压线螺孔M4
3. Current Rating: 60A  
额定电流: 60A
4. There shall be no defects such as pin deformation and burrs.  
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

**Ordering Information**

HC - \* \*\* \* - \*\*\*\* - \* \*\* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/Pin	Product No.	Material	
1.0mm Tooth (插牙)	0.8mm, 0.9mm 1.0mm, 1.1mm 1.2mm, 1.3mm 1.4mm, 1.5mm 1.6mm, 1.7mm 1.8mm, 1.9mm 2.0mm, 2.1mm 2.2mm, 2.3mm 2.4mm, 2.5mm 2.6mm, 2.7mm 2.8mm, 2.9mm 3.0mm, 3.1mm	M3 (螺牙) M4 (螺牙) M5 (螺牙) M6 (螺牙) M8 (螺牙) M10 (螺牙) M12 (螺牙) M16 (螺牙) M20 (螺牙) M24 (螺牙) M30 (螺牙) M36 (螺牙) M42 (螺牙)	0.5mm (焊脚) 0.6mm (焊脚) 0.7mm (焊脚) 0.8mm (焊脚) 0.9mm (焊脚) 1.0mm (焊脚) 1.1mm (焊脚) 1.2mm (焊脚) 1.3mm (焊脚) 1.4mm (焊脚) 1.5mm (焊脚) 1.6mm (焊脚) 1.7mm (焊脚) 1.8mm (焊脚) 1.9mm (焊脚) 2.0mm (焊脚) 2.1mm (焊脚) 2.2mm (焊脚) 2.3mm (焊脚) 2.4mm (焊脚) 2.5mm (焊脚) 2.6mm (焊脚) 2.7mm (焊脚) 2.8mm (焊脚) 2.9mm (焊脚) 3.0mm (焊脚)	08080808mm 10101010mm 12121212mm 14141414mm 16161616mm 18181818mm 20202020mm 22222222mm 24242424mm 26262626mm 28282828mm 30303030mm 32323232mm 34343434mm 36363636mm 38383838mm 40404040mm 42424242mm 44444444mm 46464646mm 48484848mm 50505050mm 52525252mm 54545454mm 56565656mm 58585858mm 60606060mm	0.5mm 0.6mm 0.7mm 0.8mm 0.9mm 1.0mm 1.1mm 1.2mm 1.3mm 1.4mm 1.5mm 1.6mm 1.7mm 1.8mm 1.9mm 2.0mm 2.1mm 2.2mm 2.3mm 2.4mm 2.5mm 2.6mm 2.7mm 2.8mm 2.9mm 3.0mm	08080808mm 10101010mm 12121212mm 14141414mm 16161616mm 18181818mm 20202020mm 22222222mm 24242424mm 26262626mm 28282828mm 30303030mm 32323232mm 34343434mm 36363636mm 38383838mm 40404040mm 42424242mm 44444444mm 46464646mm 48484848mm 50505050mm 52525252mm 54545454mm 56565656mm 58585858mm 60606060mm	08080808mm 10101010mm 12121212mm 14141414mm 16161616mm 18181818mm 20202020mm 22222222mm 24242424mm 26262626mm 28282828mm 30303030mm 32323232mm 34343434mm 36363636mm 38383838mm 40404040mm 42424242mm 44444444mm 46464646mm 48484848mm 50505050mm 52525252mm 54545454mm 56565656mm 58585858mm 60606060mm	08080808mm 10101010mm 12121212mm 14141414mm 16161616mm 18181818mm 20202020mm 22222222mm 24242424mm 26262626mm 28282828mm 30303030mm 32323232mm 34343434mm 36363636mm 38383838mm 40404040mm 42424242mm 44444444mm 46464646mm 48484848mm 50505050mm 52525252mm 54545454mm 56565656mm 58585858mm 60606060mm

		GENEAL TOLERANCE		制图	07		深圳市华灿天禄电子有限公司 ShenzhenhuacantianlueELECTRONICS CO., LTD			
		DIM	TOL	审核						
		5 or more	±0.35	批准			产品名称	PCB 焊接端子 厚度1.0 插板 铆垫片	版本	A
		2~5	±0.25	APPROVAL			TITLE	M4 4焊脚 11x10x10.2mm	REV.	
		0~2	±0.15	比例			产品料号	HC-RG1044-1110-D321-07	单位	mm
序号	变更内容	日期		SCALE			PART NO.		页次	1/1
No.	MODIFY CONTENT	MODIFY DATE		Angle	±3.0°	投影	MATERIAL		SHEET	