



- NOTES:  
备注
- 1.Brass or purple copper,Bright tin-plating  
黄铜或者紫铜, 镀亮锡
  - 2.Wire screw hole M5  
压线螺孔M5
  - 3.Current Rating: 80A  
额定电流:80A
  - 4.There shall be no defects such as pin deformation and burrs.  
不得有脚变形, 毛刺等缺陷
  - 5.Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

**Ordering Information**

HC - \* \* \* \* - \* \* \* \* - \* \* \* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Product No.	Material
① 插针 (Pin)	① 1.5mm	① M5 (M5)	① 1.5mm	100/12x11.5mm	① 1212-D702-07	① 黄铜 (Brass)
② 螺母 (Nut)	② 1.5mm	② M5 (M5)	② 1.5mm	.....	② 1212-D702-07	② 紫铜 (Purple Copper)
③ 螺柱 (Screw)	③ 1.5mm	③ M5 (M5)	③ 1.5mm	.....	③ 1212-D702-07	③ 黄铜 (Brass)
④ 螺柱 (Screw)	④ 1.5mm	④ M5 (M5)	④ 1.5mm	.....	④ 1212-D702-07	④ 紫铜 (Purple Copper)

		GENEAL TOLERANCE		制图	07		
		DIM	TOL	审核			
		5 or more	±0.35	批准			
		2~5	±0.25	比例	产品名称 PCB 焊接端子 厚度1.5 插板 铆垫片		
		0~2	±0.15	SCALE	M5 4焊脚 12x12x11.5mm		
		Angle	±3.0°	投影	产品料号	HC-RG1554-1212-D702-07	版本
序号	变更内容	日期			PART NO.		REV.
No.	MODIFY CONTENT	MODIFY DATE			MATERIAL		UNITS
							mm
							页次
							SHEET
							1/1

**深圳市华灿天禄电子有限公司**  
ShenzhenhuacantianluELECTRONICS CO., LTD