


PCB 参考安装方式



NOTES:

备注

1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 60A
额定电流: 60A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - * - * - * - * - * - 07

Type	Thickness	Screw	Welding	Series	Model	Product No.	Material
Welding Tooth (焊脚)	0.5±0.1mm	0.8 (螺牙)	(焊脚)	08080808mm	Model (焊脚)	Product No. (产品序号)	Material (材料)
Welding Nut (焊螺母)	1.0±0.1mm	1.0 (螺牙)	(焊脚)	1.0±0.1mm	Model (焊脚)	Product No. (产品序号)	Material (材料)
Welding Gasket (焊垫片)	1.5±0.1mm	1.5 (螺牙)	(焊脚)	1.5±0.1mm	Model (焊脚)	Product No. (产品序号)	Material (材料)
	2.0±0.1mm	2.0 (螺牙)	(焊脚)	2.0±0.1mm	Model (焊脚)	Product No. (产品序号)	Material (材料)
	2.5±0.1mm	2.5 (螺牙)	(焊脚)	2.5±0.1mm	Model (焊脚)	Product No. (产品序号)	Material (材料)
	3.0±0.1mm	3.0 (螺牙)	(焊脚)	3.0±0.1mm	Model (焊脚)	Product No. (产品序号)	Material (材料)

		GENREL TOLERANCE		制图	07		深圳市华灿天禄电子有限公司 ShenzhenhuacantianlueELECTRONICS CO., LTD			
		DIM	TOL	审核			产品名称	PCB 焊接端子 厚度1.0 插板 铆垫片	版本	A
		5 or more	±0.35	CHECK			TITLE	M4 4焊脚 8x8x15.2mm	REV.	
		2~5	±0.25	批 准			产品料号	HC-RG1044-0808-D304-07	单 位	mm
		0~2	±0.15	APPROVAL			PART NO.		UNITS	
1	初版发行			比 例					页 次	1/1
序号	变更内容	日期		SCALE			材料		SHEET	
No.	MODIFY CONTENT	MODIFY DATE		Angle			MATERIAL			
				投影						