



NOTES:
备注

1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 60A
额定电流: 60A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw	Welding Feet	Series	Pin/P	Product No.	Material
Pin (插脚)	0.8±0.1mm	Ø1.0 (螺牙)	2个	1620#16x20mm	Pin	产品序号	镀锡铜 (黄铜)
Pin Nut (螺母)	1.0±0.1mm	Ø1.0 (螺牙)	2个	Pin		镀锡铜 (黄铜)
Pin Gasket (垫片)	1.5±0.1mm	Ø1.0 (螺牙)	4个		Dip		镀锡铜 (黄铜)
	2.0±0.1mm	Ø1.0 (螺牙)	6个				
	2.5±0.1mm	Ø1.0 (螺牙)	8个				
	3.0±0.1mm	Ø1.0 (螺牙)				

			GENEAL TOLERANCE	制图	07			深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
			DIM TOL	审核							
			5 or more ±0.35	批准				产品名称 PCB 焊接端子 厚度1.0 插板 铆垫片			
			2~5 ±0.25	APPROVAL				M4 4焊脚 10x8x13.2mm			
			0~2 ±0.15	比例				版本 REV.			
			Angle ±3.0°	SCALE				A			
序号	变更内容	日期		投影				产品料号	HC-RG1044-1008-D308-07	单位	mm
No.	MODIFY CONTENT	MODIFY DATE		Projection				材料		页次	1/1
								SHEET			