



NOTES:

备注

1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 60A
额定电流: 60A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/P	Product No.	Material
Pin (插脚)	0.5±0.05mm	0.8±0.05mm	0.5mm	1608888mm	Pin	产品序号	镀锡铜
Pin Nut (插脚螺母)	1.0±0.05mm	1.0±0.05mm	0.5mm	Pin	镀锡铜
Pin Gasket (插脚垫片)	1.5±0.05mm	1.5±0.05mm	0.5mm	Pin	镀锡铜
Pin Gasket (插脚垫片)	2.0±0.05mm	2.0±0.05mm	0.5mm	Pin	镀锡铜
Pin Gasket (插脚垫片)	2.5±0.05mm	2.5±0.05mm	0.5mm	Pin	镀锡铜
Pin Gasket (插脚垫片)	3.0±0.05mm	3.0±0.05mm	0.5mm	Pin	镀锡铜

		GENREL TOLERANCE		制图	07			
		DIM	TOL	审核	深圳市华灿天禄电子有限公司			
		5 or more	±0.35	CHECK	ShenzhenhuacantianluELECTRONICS CO.,LTD			
		2~5	±0.25	批准	产品名称	PCB 焊接端子 厚度1.0 插板 铆垫片	版本	A
		0~2	±0.15	APPROVAL	TITLE	M4 4焊脚 8x8x9.2mm	REV.	
		Angle	±3.0°	比例	产品料号	HC-RG1044-0808-D301-07	单位	mm
序号	变更内容	日期		SCALE	PART NO.		页次	1/1
No.	MODIFY CONTENT	MODIFY DATE		投影	MATERIAL		SHEET	

