



NOTES:

备注

1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 70A
额定电流: 70A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	INCLIP	Product No.	Material
插板齿 (插牙)	0.8±0.1mm	M3 (螺牙)	(焊脚)	1620#16x20mm	插板	产品序号	默认Copper (黄铜)
螺帽 (螺帽)	1.0±0.1mm	M4 (螺牙)	2x2个	插板		镀亮铜 (镀铜)
螺柱 (螺柱)	1.5±0.1mm	M4 (螺牙)	4x4个		Dip		
螺垫 (螺垫)	2.0±0.1mm	M6 (螺牙)	6x6个				
	2.5±0.1mm		8x8个				
	3.0±0.1mm						

PCB 参考安装方式

		GENERAL TOLERANCE	制图	07	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD		
		DIM TOL	审核		产品名称	PCB 焊接端子 厚度1.2 插板 铆垫片	版本
		5 or more ±0.35	CHECK		TITLE	M4 4焊脚 9x9x10.5mm	REV.
		2~5 ±0.25	批准		产品料号	HC-RG1244-0909-D502-07	UNIT
		0~2 ±0.15	APPROVAL		PART NO.		mm
		Angle ±3.0°	比例		材料		UNIT
序号	变更内容	日期	投影		MATERIAL		REV.
No.	MODIFY CONTENT	MODIFY DATE	Projection				SHEET
							1/1