



NOTES:

备注

1. Brass or purple copper, matte tin-plating  
黄铜或紫铜，镀雾锡
2. Wire screw hole M4  
压线螺孔M4
3. Current Rating: 60A  
额定电流:60A
4. Screw Hole Standard Torque: 13 lbf.in  $\approx$  1.47 N/m  
螺孔标准扭矩: 13 lbf.in  $\approx$  1.47 N/m
5. Operating Temperature:  $-40^{\circ}\text{C}^{\sim}+125^{\circ}\text{C}$   
工作温度: $-40^{\circ}\text{C}^{\sim}+125^{\circ}\text{C}$
6. Has passed the 72 hour salt spray test  
已通过72小时盐雾测试
7. There shall be no defects such as pin deformation and burrs.  
不得有脚变形，毛刺等缺陷
8. Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

**Ordering Information**

HC - \* \*\* \* \* - \*\*\*\* - D \*\*\* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	D-BIP	Product No.	Material
M-Full Teeth (抽牙)	08-0.8mm	3-M3 (螺牙)	0808-8x8mm	DIP	产品序号	默认=Copper (黄铜)	
M-Nut (螺母)	10-1.0mm	4-M4 (螺牙)	1010-10x10mm	SMT		BC=Red Copper (紫铜)	
M-Gasket (垫片)	12-1.2mm	5-M5 (螺牙)	1212-12x12mm	FD-Flag Dip			
	15-1.5mm	6-M6 (螺牙)	1515-15x15mm				
	20-2.0mm		20-2.0mm				
	25-2.5mm		25-2.5mm				
	30-3.0mm		30-3.0mm				
	32-3.2mm		32-3.2mm				

			GENEAL TOLERANCE	制图	07	深圳市华灿天禄电子有限公司 ShenzhenhuaciantianluELECTRONICS CO.,LTD			
			DIM TOL	审核					
			5 or more $\pm 0.35$	批准		TITLE	M4 4焊脚 9.1x9.1x10.5mm	REV.	
			2~5 $\pm 0.25$	APPROVAL		PART NO.	HC-M1244-0909-D529-07	UNIT	mm
			0~2 $\pm 0.15$	比例		MATERIAL		SHEET	1/1
序号	变更内容	日期	Angle $\pm 3.0^{\circ}$	投影					
No.	MODIFY CONTENT	MODIFY DATE							