



- NOTES:
备注
1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
 2. Wire screw hole M5
压线螺孔M5
 3. Current Rating: 100A
额定电流: 100A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - * - * - * - * - * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Part	Product No.	Material
插脚 (Pin)	0.8mm	M5	100mm/100mm	1520	1520	HC-RG1556-1520-D716-07	黄铜 (Brass)
插脚 (Pin)	1.5mm	M5	100mm/100mm	1520	1520	HC-RG1556-1520-D716-07	紫铜 (Purple Copper)
插脚 (Pin)	2.5mm	M5	100mm/100mm	1520	1520	HC-RG1556-1520-D716-07	紫铜 (Purple Copper)
插脚 (Pin)	3.5mm	M5	100mm/100mm	1520	1520	HC-RG1556-1520-D716-07	紫铜 (Purple Copper)

		GENEAL TOLERANCE		制图	07		深圳市华灿天禄电子有限公司 ShenzhenhuacantianlueLECTRONICS CO., LTD			
		DIM	TOL	审核						
		5 or more	±0.35	批准			产品名称	PCB 焊接端子 厚度1.5 插板 铜垫片	版本	A
		2~5	±0.25	APPROVAL			TITLE	M5 6焊脚 15x20x14mm	REV.	
		0~2	±0.15	比例			产品料号	HC-RG1556-1520-D716-07	单位	mm
		Angle	±3.0°	SCALE			PART NO.		页次	1/1
序号	变更内容	日期	投影				MATERIAL		SHEET	
No.	MODIFY CONTENT	MODIFY DATE								