



NOTES:

备注

1. Brass or purple copper, Bright tin-plating  
黄铜或者紫铜, 镀亮锡
2. Wire screw hole M6  
压线螺孔M6
3. Current Rating: 120A  
额定电流:120A
4. There shall be no defects such as pin deformation and burrs.  
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

Ordering Information

HC - \* \*\* \* - \*\*\*\* - \* \*\* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/P	Product No.	Material
Wire Lead Tooth (插牙)	0.8~1.0mm	Φ4.0 (螺牙)	深脚	0908#16x8mm	Pin/P	产品序号	镀锡铜 (美标)
Rivet Nut (铆螺母)	1.0~1.2mm	Φ4.0 (螺牙)	Φ2个	1620#16x20mm	Pin/P		镀锡铜 (美标)
Rivet Gasket (铆垫片)	1.5~1.7mm	Φ4.0 (螺牙)	Φ4个	.....	Pin/P		镀锡铜 (美标)
	2.0~2.2mm	Φ4.0 (螺牙)	Φ6个				
	2.5~2.7mm	Φ4.0 (螺牙)	Φ8个				
	3.0~3.2mm	Φ4.0 (螺牙)	Φ8个				

		GENERAL TOLERANCE		制图	07		深圳市华灿天禄电子有限公司 ShenzhenuacantianluELECTRONICS CO., LTD			
		DIM	TOL	审核			产品名称	PCB 焊接端子 厚度1.5 插板 铆垫片	版本	A
		5 or more	±0.35	CHECK			TITLE	M6 6焊脚 15x20x17mm	REV.	
		2~5	±0.25	批准			产品料号	HC-RG1566-1520-D724-07	单位	mm
		0~2	±0.15	APPROVAL			PART NO.		页次	1/1
序号	变更内容	日期	投影			材料				
No.	MODIFY CONTENT	MODIFY DATE	Angle	±3.0°		MATERIAL				