



NOTES:

- 备注
1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
 2. Wire screw hole M6
压线螺孔M6
 3. Current Rating: 180A
额定电流: 180A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * * * * - * * * * - * * * * - 07

Type	Thickness	Screw Thread	Welding Foot	Series	Plating	Product No.	Material
插板端子 (插板)	1.0mm	M6	2mm	1620=16.20mm	光亮	产品序号	黄铜或紫铜
压线螺孔	1.0mm	M6	2mm	光亮	黄铜或紫铜
焊脚	1.0mm	M6	2mm	光亮	黄铜或紫铜
插板端子	1.0mm	M6	2mm	光亮	黄铜或紫铜

		GENEAL TOLERANCE		制图	07		
		DIM	TOL	审核			
		5 or more	±0.35	批准			
		2~5	±0.25	比例			
		0~2	±0.15	SCALE			
序号	变更内容	日期		投影			
No.	MODIFY CONTENT	MODIFY DATE			产品名称	PCB 焊接端子 厚度2.0 插板 铆垫片	版本
					TITLE	M6 8焊脚 16x20x21mm	REV.
					产品料号	HC-RG2068-1620-D904-07	单位
					PART NO.		mm
					材料		页次
					MATERIAL		SHEET
							1/1

深圳市华灿天禄电子有限公司
ShenzhenhuacantianluELECTRONICS CO., LTD