



NOTES:

- 备注
1. Brass or purple copper, matte tin-plating
黄铜或紫铜, 镀雾锡
 2. Wire screw hole M4
压线螺孔M4
 3. Current Rating: 50A
额定电流: 50A
 4. Screw Hole Standard Torque: 13 lbf. in \approx 1.47 N/m
螺孔标准扭矩: 13 lbf. in \approx 1.47 N/m
 5. Operating Temperature: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$
工作温度: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$
 6. Has passed the 72 hour salt spray test
已通过72小时盐雾测试
 7. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 8. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * * - **** - D *** * - 07

Type	Thickness	Screw	Welding Feet	Series	D=DFP	Product No.	Material
#Pin1 Teeth (抽牙)	08-0.8mm 10-1.0mm 12-1.2mm 15-1.5mm 20-2.0mm 25-2.5mm 30-3.0mm 35-3.2mm	3-M3 (螺牙)	(焊脚)	0808-8x8mm 1620-16x20mm	S=SBT FD=Flag Dip	产品序号	默认=Copper (黄铜) BC=Red Copper (紫铜)
RN=Rivet Nut (铆螺母)		4-M4 (螺牙)	2-2个				
RG=Rivet Gasket (铆垫片)		5-M5 (螺牙)	4-4个				
		6-M6 (螺牙)	6-6个				
			8-8个				

			GENEAL TOLERANCE	制 图	07	深圳市华灿天禄电子有限公司 ShenzhenhuaciantianluELECTRONICS CO., LTD			
			DIM TOL	审 核					
			5 or more ± 0.35	批 准		产品名称	PCB 焊接端子 厚度1.0 插板 抽牙	版 本	A
			2~5 ± 0.25	APPROVAL		TITLE	M4 4焊脚 8x8x11.2mm	REV.	
			0~2 ± 0.15	比 例		产品料号	HC-M1044-0808-D328-07	单 位	mm
			Angle $\pm 3.0^{\circ}$	投 影		PART NO.		页 次	1/1
序号	变更内容	日期		Projection		MATERIAL		SHEET	
No.	MODIFY CONTENT	MODIFY DATE							