



NOTES:

备注

- Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
- Wire screw hole M5/M6
压线螺孔M5/M6
- Current Rating: 100A
额定电流: 100A
- There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
- Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - D *** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Product No.	Material
插脚	0.5mm	M5/M6	1.5mm	14.5x14.5x12mm	HC-RG15X6-1414-D057-07	铜垫片

			GENEAL TOLERANCE	制图	07		
			DIM TOL	审核			
			5 or more ±0.35	批准			
			2~5 ±0.25	APPROVAL			
			0~2 ±0.15	比例			
			Angle ±3.0°	SCALE			
序号	变更内容	日期		投影			
No.	MODIFY CONTENT	MODIFY DATE		Projection	产品名称	PCB 焊接端子 厚度1.5 插板 铜垫片	版本
					TITLE	M5/M6 6焊脚 14.5x14.5x12mm	REV.
					产品料号	HC-RG15X6-1414-D057-07	单位
					PART NO.		UNITS
					材料		mm
					MATERIAL		页次
							SHEET
							1/1

深圳市华灿天禄电子有限公司
ShenzhenhuacantianlueELECTRONICS CO., LTD