



- NOTES:  
备注
1. Brass or purple copper, Bright tin-plating  
黄铜或紫铜, 镀亮锡
  2. Wire screw hole M5  
压线螺孔M5
  3. Current Rating: 100A  
额定电流:100A
  4. There shall be no defects such as pin deformation and burrs.  
不得有脚变形, 毛刺等缺陷
  5. Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

**Ordering Information**

HC - \* \* \* \* - \* \* \* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Part No.	Product No.	Material
插片 (插片)	0.5, 0.8mm	M2, M2.5, M3, M3.5, M4, M4.5, M5, M6, M8	焊脚 (焊脚)	0100#0.5mm, 1620#1.6x20mm	0100#0.5mm, 1620#1.6x20mm	产品序号	黄铜 (紫铜)
螺母 (螺母)	0.5, 0.8mm	M2, M2.5, M3, M3.5, M4, M4.5, M5, M6, M8	焊脚 (焊脚)	.....	.....	产品序号	黄铜 (紫铜)
焊脚 (焊脚)	0.5, 0.8mm	M2, M2.5, M3, M3.5, M4, M4.5, M5, M6, M8	焊脚 (焊脚)	.....	.....	产品序号	黄铜 (紫铜)
焊脚 (焊脚)	0.5, 0.8mm	M2, M2.5, M3, M3.5, M4, M4.5, M5, M6, M8	焊脚 (焊脚)	.....	.....	产品序号	黄铜 (紫铜)

		GENEAL TOLERANCE		制图	07		<b>深圳市华灿天禄电子有限公司</b> ShenzhenhuacantianluELECTRONICS CO., LTD		
		DIM	TOL	审核					
		5 or more	±0.35	批准	产品名称		PCB 焊接端子 厚度1.5 插板 铜垫片	版本	A
		2~5	±0.25	APPROVAL	TITLE		M5 4焊脚 16x20x14mm	REV.	
		0~2	±0.15	比例	PART NO.		HC-RG1554-1620-D720-07	UNIT	mm
1	初版发行	日期		SCALE	MATERIAL			SHEET	1/1
序号	变更内容	MODIFY DATE		投影					