



NOTES:
备注

1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 70A
额定电流: 70A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/P	Product No.	Material
Pin (插针)	0.8±0.05mm	M3 (螺牙)	22个	1620#16x20mm	Pin	产品序号	镀亮铜 (黄铜)
Pin Nut (螺母)	1.0±0.05mm	M3 (螺牙)	22个	Pin	镀亮铜 (紫铜)
Pin Gasket (垫片)	1.5±0.05mm	M3 (螺牙)	4个	Pin
Pin Gasket	2.0±0.05mm	M3 (螺牙)	6个	Pin
Pin Gasket	2.5±0.05mm	M3 (螺牙)	8个	Pin
Pin Gasket	3.0±0.05mm	M3 (螺牙)	Pin

		GENERAL TOLERANCE		制图	07			深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
		DIM	TOL	审核				产品名称	PCB 焊接端子 厚度1.2 插板 铆垫片	版本	A
		5 or more	±0.35	批准				TITLE	M4 4焊脚 11x9x13.5mm	REV.	
		2~5	±0.25	比例				产品料号	HC-RG1244-1109-D509-07	单位	mm
		0~2	±0.15	投影				PART NO.		页次	1/1
序号	变更内容	日期		Projection				MATERIAL		SHEET	
No.	MODIFY CONTENT	MODIFY DATE									