



NOTES:  
备注

1. Brass or purple copper, Bright tin-plating  
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4  
压线螺孔M4
3. Current Rating: 70A  
额定电流: 70A
4. There shall be no defects such as pin deformation and burrs.  
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

**Ordering Information**

HC - \* \*\* \* - \*\*\*\* - \* \*\* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Model	Product No.	Material
Pin (插针)	0.8±0.05mm	0.8±0.05mm	0.8±0.05mm	1620	1620	1620	Brass (黄铜)
Pin with Nut (带螺母插针)	1.0±0.05mm	1.0±0.05mm	1.0±0.05mm	1620	1620	1620	Purple Copper (紫铜)
Pin with Gasket (带垫片插针)	1.5±0.05mm	1.5±0.05mm	1.5±0.05mm	1620	1620	1620	Brass (黄铜)
	2.0±0.05mm	2.0±0.05mm	2.0±0.05mm	1620	1620	1620	Purple Copper (紫铜)
	2.5±0.05mm	2.5±0.05mm	2.5±0.05mm	1620	1620	1620	Brass (黄铜)
	3.0±0.05mm	3.0±0.05mm	3.0±0.05mm	1620	1620	1620	Purple Copper (紫铜)

PCB 参考安装方式

			GENEAL TOLERANCE	制图	07	深圳市华灿天禄电子有限公司 ShenzhenhuacuantianlueLECTRONICS CO., LTD			
			DIM TOL	审核		产品名称	PCB 焊接端子 厚度1.2 插板 铆垫片	版本	A
			5 or more ±0.35	CHECK		TITLE	M4 4焊脚 12x9x13.5mm	REV.	
			2~5 ±0.25	批准		产品料号	HC-RG1244-1209-D514-07	单位	mm
			0~2 ±0.15	APPROVAL		PART NO.		页次	1/1
1	初版发行		Angle ±3.0°	SCALE		材料		SHEET	
序号	变更内容	日期		投影		MATERIAL			
No.	MODIFY CONTENT	MODIFY DATE							