



- NOTES:
备注
1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
 2. Wire screw hole M4
压线螺孔M4
 3. Current Rating: 60A
额定电流:60A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/Pin	Product No.	Material
Pin (插针)	0.8±0.05mm	0.8 (螺牙)	2个	1620#16x20mm	Pin	产品序号	紫铜 (紫铜)
Pin Nut (插针螺母)	1.0±0.05mm	0.8 (螺牙)	2个	Pin	紫铜 (紫铜)
Pin Gasket (插针垫片)	1.5±0.05mm	0.8 (螺牙)	4个	紫铜 (紫铜)
	2.0±0.05mm	0.8 (螺牙)	6个	紫铜 (紫铜)
	2.5±0.05mm	0.8 (螺牙)	8个	紫铜 (紫铜)
	3.0±0.05mm	0.8 (螺牙)	紫铜 (紫铜)

			GENEAL TOLERANCE	制图	07	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM TOL	审核		产品名称	PCB 焊接端子 厚度1.0 插板 铆垫片	版本	A
			5 or more ±0.35	CHECK		TITLE	M4 4焊脚 10x8x15.2mm	REV.	
			2~5 ±0.25	批准		产品料号	HC-RG1044-1008-D309-07	单位	mm
			0~2 ±0.15	APPROVAL		PART NO.		页次	1/1
1	初版发行		Angle ±3.0°	SCALE		MATERIAL		SHEET	
序号	变更内容	日期		投影					
No.	MODIFY CONTENT	MODIFY DATE							