



NOTES:

- 备注
1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
 2. Wire screw hole M5
压线螺孔M5
 3. Current Rating: 100A
额定电流:100A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * * * * - * * * * - * * * * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Product No.	Material
插板 (插脚)	0.4mm	M5 (螺牙)	180° (焊脚)	18x14x14mm	HC-RG1554-1814-D713-07	黄铜 (紫铜)
螺母 (螺帽)	0.4mm	M5 (螺牙)	180° (焊脚)	18x14x14mm	HC-RG1554-1814-D713-07	黄铜 (紫铜)
焊脚 (焊脚)	0.4mm	M5 (螺牙)	180° (焊脚)	18x14x14mm	HC-RG1554-1814-D713-07	黄铜 (紫铜)
焊脚 (焊脚)	0.4mm	M5 (螺牙)	180° (焊脚)	18x14x14mm	HC-RG1554-1814-D713-07	黄铜 (紫铜)

			GENERAL TOLERANCE	制图	07		
			DIM TOL	审核			
			5 or more ±0.35	批准			
			2~5 ±0.25	比例			
			0~2 ±0.15	投影			
			Angle ±3.0°				
1	初版发行	日期					
序号	变更内容	日期		产品名称	PCB 焊接端子 厚度1.5 插板 铆垫片	版本	A
No.	MODIFY CONTENT	MODIFY DATE		TITLE	M5 4焊脚 18x14x14mm	REV.	
				产品料号	HC-RG1554-1814-D713-07	单位	mm
				MATERIAL		页次	1/1
						SHEET	

深圳市华灿天禄电子有限公司
ShenzhenhuacantianlueLECTRONICS CO., LTD