



- NOTES:
备注
- 1.Brass or purple copper,Bright tin-plating
黄铜或紫铜，镀亮锡
 - 2.Wire screw hole M5
压线螺孔M5
 - 3.Current Rating: 100A
额定电流:100A
 - 4.There shall be no defects such as pin deformation and burrs.
不得有脚变形，毛刺等缺陷
 - 5.Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * * - * * * * - * * * * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Product No.	Material
插脚 (插脚)	0.4mm	M5 (螺牙)	0.5mm	1520-1520mm	1520-1520mm	黄铜 (黄铜)
螺母 (螺母)	1.2mm	M5 (螺牙)	0.5mm	紫铜 (紫铜)
焊脚 (焊脚)	1.2mm	M5 (螺牙)	0.5mm	紫铜 (紫铜)
焊脚 (焊脚)	1.2mm	M5 (螺牙)	0.5mm	紫铜 (紫铜)

		GENEAL TOLERANCE		制图	07		深圳市华灿天禄电子有限公司 ShenzhenhuacuantianluELECTRONICS CO.,LTD			
		DIM	TOL	审核			产品名称	PCB 焊接端子 厚度1.5 插板 铜垫片	版本	A
		5 or more	±0.35	CHECK			TITLE	M5 6焊脚 15x20x22mm	REV.	
		2~5	±0.25	批准			产品料号	HC-RG1556-1520-D718-07	单位	mm
		0~2	±0.15	APPROVAL			PART NO.		页次	1/1
1	初版发行			比例			MATERIAL		SHEET	
序号	变更内容	日期		SCALE						
No.	MODIFY CONTENT	MODIFY DATE		投影						