



NOTES:

备注

1. Copper, Bright tin plated  
黄铜, 镀亮镍
2. Wire screw hole M4  
压线螺孔M4
3. Current Rating: 45A  
额定电流: 45A
4. There shall be no defects such as pin deformation and burrs.  
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

Ordering Information

HC - \* \*\* \* - \*\*\*\* - \* \*\* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/Pin	Product No.	Material
Pin (插脚)	0.8±0.05mm	M4 (螺牙)	2mm (焊脚)	1620#16x20mm	Pin	产品序号	黄铜 (Copper)
Pin Nut (插脚螺母)	1.0±0.05mm	M4 (螺牙)	2mm (焊脚)	.....	Pin		镀亮镍黄铜 (Bright Tin Plated Copper)
Pin Gasket (插脚垫片)	1.5±0.05mm	M4 (螺牙)	2mm (焊脚)		Dip		黄铜 (Copper)
	2.0±0.05mm	M4 (螺牙)	2mm (焊脚)				
	2.5±0.05mm	M4 (螺牙)	2mm (焊脚)				
	3.0±0.05mm	M4 (螺牙)	2mm (焊脚)				

		GENREL TOLERANCE		制图	07		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
		DIM	TOL	审核			产品名称	PCB焊接端子 厚度0.8 插板 铆垫片	版本	A
		5 or more	±0.35	批准			TITLE	M4 4焊脚 8x8x15.2mm	REV.	
		2~5	±0.25	比例			产品料号	HC-RG0844-0808-D206-07	单位	mm
		0~2	±0.15	投影			PART NO.		页次	1/1
序号	变更内容	日期				MATERIAL		UNITS	SHEET	
No.	MODIFY CONTENT	MODIFY DATE								