



NOTES:

备注

1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 60A
额定电流: 60A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type Type (型号)	Thickness 0.5mm 1.0mm 1.5mm 2.0mm 2.5mm 3.0mm	Screw 0#3 (螺牙) 0#4 (螺牙) 0#6 (螺牙) 0#8 (螺牙)	Welding Feet 2mm 3mm 4mm 5mm 6mm 8mm	Series 080888mm 16201620mm	Pin/P SMT Flag Dip	Product No. 产品序号	Material Material (黄铜) (紫铜)
----------------------	---	---	---	---	-----------------------------	---------------------	--------------------------------------

PCB 参考安装方式

			GENEAL TOLERANCE	制图	07			深圳市华灿天禄电子有限公司 ShenzhenhuacantianlueLECTRONICS CO., LTD		
			DIM TOL	审核				产品名称 PCB 焊接端子 厚度1.0 插板 铆垫片 TITLE M4 4焊脚 11x10x13.2mm		
			5 or more ±0.35	批准				版本号 REV. A 产品料号 PART NO. HC-RG1044-1110-D323-07		
			2~5 ±0.25	比例				单位 UNITS mm 页次 SHEET 1/1		
			0~2 ±0.15	投影						
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle ±3.0°	投影						