



NOTES:

- 备注
1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
 2. Wire screw hole M5
压线螺孔M5
 3. Current Rating: 70A
额定电流: 70A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin Pitch	Product No.	Material
Weld Tooth (焊牙)	0.6~0.8mm	0.6~0.8 (螺牙)	0.6~0.8 (焊脚)	0908#16mm	0.5mm	产品序号	镀锡黄铜 (美标)
Rivet Nut (铆螺母)	1.0~1.0mm	1.0~1.0 (螺牙)	1.0~1.0 (焊脚)	1620#16x20mm	0.5mm		镀锡黄铜 (美标)
Rivet Nut (铆螺母)	1.2~1.2mm	1.2~1.2 (螺牙)	1.2~1.2 (焊脚)	0.5mm		镀锡黄铜 (美标)
Rivet Gasket (铆螺母)	1.5~1.5mm	1.5~1.5 (螺牙)	1.5~1.5 (焊脚)	0.5mm		镀锡黄铜 (美标)
Rivet Gasket (铆螺母)	2.0~2.0mm	2.0~2.0 (螺牙)	2.0~2.0 (焊脚)	0.5mm		镀锡黄铜 (美标)
Rivet Gasket (铆螺母)	2.5~2.5mm	2.5~2.5 (螺牙)	2.5~2.5 (焊脚)	0.5mm		镀锡黄铜 (美标)
Rivet Gasket (铆螺母)	3.0~3.0mm	3.0~3.0 (螺牙)	3.0~3.0 (焊脚)	0.5mm		镀锡黄铜 (美标)

		GENERAL TOLERANCE		制图	07			
		DIM	TOL	审核	深圳市华灿天禄电子有限公司			
		5 or more	±0.35	CHECK	ShenzhenhuacantianluELECTRONICS CO., LTD			
		2~5	±0.25	批准	产品名称	PCB 焊接端子 厚度1.2 贴片 抽牙	版本	A
		0~2	±0.15	APPROVAL	TITLE	M5 4焊脚 40x11.5x7.9mm	REV.	
		Angle	±3.0°	比例	产品料号	HC-M1254-4011-S528-07	单位	mm
序号	变更内容	日期		SCALE	PART NO.		页次	1/1
No.	MODIFY CONTENT	MODIFY DATE		投影	MATERIAL		SHEET	