



NOTES:

MATERIAL:

1. HOUSING MATERIAL :GLASS FILLED POLYESTER UL94V-0.
2. CONTACT MATERIAL :PHOSPHOR BRONZE  $\phi=0.46\text{mm}$ .
3. PLATING : GOLD PLATING  $3\mu\sim 50\mu$  OVER NICKEL.

ELECTRICAL:

1. VOLTAGE RATING :125 VAC RMS.
2. CURRENT RATING :1.5 AMP.
3. CONTACT RESISTANCE :30 MILLIOHMS MAX.
4. INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC .
5. DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 50Hz. 1MIN.

MECHANICAL:

1. DURRABILITY :750 CYCLES MIN.
2. PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

1. STORAGE : -40° C TO 85° C.
2. OPERATION : 0° C TO 70° C.

		GENEAL TOLERANCE		制 图 DRAWING	03		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD				
		DIM TOL		审 核 CHECK							
		X. X ±0.30		批 准 APPROVAL			产品名称 TITLE	网络插座 (全塑 8P/8C 无灯无弹)		版本 REV.	A
1		初版发行		比 例 SCALE			产品料号 PART NO.	HC-RJ11-052A-1-6-03		单 位 UNITS	mm
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle ±3.0°	投 影 Projection			材 料 MATERIAL			页 次 SHEET	1/1