



. NOTES
ELECTRICAL
1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 40 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 100V DC.
5. DIELECTRIC DIELECTRIC RESISTANCE : 500V DC RMS 50Hz. 1MIN.

. MECHANICAL
1. DURRABILITY : 750 CYCLES MIN.
2. MATING/UNMATING FORC : 2.24 KG. F MAX.

. ENVIRONMENTAL:
1. OPERATION : -40°C~+85°C.
2. STORAGE : -40°C~+85°C.

. THE DIMENSIONS WITH "▼" MARK ARE CRITICAL AND SHOULD BE CONTROLLED BY QC.

. PIN ASSIGNMENT:		
PLN	NAME	DESCRIPTION
1	TX+	D1+ Transceive Data+
2	TX-	D1- Transceive Data-
3	RX+	D2+ Transceive Data+
4	BI	D3+ Bi-directional data+
5	BI	D3- Bi-directional data-
6	RX-	D2- Transceive Data-
7	BI	D4+ Bi-directional data+
8	BI	D4- Bi-directional data-

3	TERMINAL	8	RJ45 180度短体 DIP端子 C5191 镀成: 45' u Min 焊锡区: 80u' Min Sn, 接触区F' U GOLD
2	INSERT MOLDING	1	立式短体DIP2.54端子molding半成品FU
1	HOUSING	1	主体 RJ45 180度短体 LCP 黑色 无灯香菇柱 UL94V-0
NO.	PART NAME	Q' TY	MATERIAL (PLATING & COLOR)

			GENEAL TOLERANCE	制 图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD				
			DIM	TOL	审 核 CHECK	产品名称 TITLE	网络插座 (立插 无灯全塑 H12.7 黑色 LCP)	版 本 REV.	A
			X.X	±0.30	批 准 APPROVAL	产品料号 PART NO.	HC-RJ45-140D-1-6-02	单 位 UNITS	mm
			X.XX	±0.20	比 例 SCALE	材料 MATERIAL		页 次 SHEET	1/1
			X.XXX	±0.10	投 影 Projection				
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°					