


LED Specification

Standard LED Color	LED Wavelength	Foward(A)	Foward(V)
Yellow	568nm	20mA	1.85-2.45V
Green	585nm	20mA	1.7-2.2V



MATERIAL:
 HOUSING:PA46,PBT,BLACK.
 TERMINAL: PHOSPHOR BRONZE Ø0.46MM
 G/FU" GOLD PLATING

SHIELD:C2680,T=0.20MM, 20 MIN NICKEL PLATING
 NO ALL AREA

MACHANICAL:
 DURABILITY: 750 CYCLES MIN,12.5MM/MINUTE.
 INSERTION FORCE: 2.2KG.F MAX.
 RETENTION STRENGTH : 7.7KG.F BETWEEN JACK AND PLUG.
 OPERATING TEMPERATURE: -40 °C~+85 °C.
 STORAGE TEMPERATURE: -40°C~+85°C.
 ALL CRITICAL DIMENSIONS WITH "*"

VOLTAGE: 125 VOLTS AC.
 CURRENT RATING : 1.5AMP.
 DIELECTRIC STRENGTH: 1000 VAC RMS 50HZ OR 60HZ,1MIN.
 INSULATION RESISTANCE: 500 MEGA OHMS MIN. INITIAL
 AFTER 500V DC FOR 1 MINUTE.
 CONTACT RESISTANCE: SINGLE TERMINAL 30 MILLIOHMS MAX.
 INITIAL 50 MILLIOHMS MAX. AFTER
 DURABILITY TEST.

			GENEERL TOLERANCE	制图	深圳市华灿天禄电子有限公司			
			DIM TOL	审核	ShenzhenhuacantianluELECTRONICS CO., LTD			
			X.X ±0.30	批准	产品名称	网络插座 (2x1 带灯带弹)	版本	A
			X.XX ±0.20	比例	产品料号	HC-RJ45-059D-2x1-1-04	单位	mm
			X.XXX ±0.10	投影	材料		页次	1/1
序号	变更内容	日期	Angle ±3.0°	Projection			页次	1/1
No.	MODIFY CONTENT	MODIFY DATE					SHEET	