



- NOTES:
- MATERIAL:
 - HOUSING: LCP ,COLOR IS BLACK;
 - CONTACT: PHOSPHOR COPPER(T=0.3MM) ;
 - SHELL: SUS (T=0.2mm) ;
 - FINISH: GOLD PLATED G/Fu⁺;
 - ELECTRICAL:
 - VOLTAGE RATING: 125 VAC RMS;
 - CURRENT RATING: 1.5 AMP;
 - CONTACT RESISTANCE: 35MILLIOHMS MAX.;
 - WITHSTAND VOLTAGE: 500 VAC RMS 50(60)Hz,1MIN.;
 - INSULATION RESISTANCE: 500MEGHOHMS MIN @500V DC.;
 - MECHANICAL:
 - MATING/UNMATING FORCE: 22N MAX.;
 - RETENTION STRENGTH: 50N MIN.;
 - OPERATING LIFE: 750 CYCLES MIN.;
 - ENVIRONMENTAL:
 - STORAGE TEMPERATURE RANGE: -40°C~+85°C;
 - OPERATION TEMPERATURE RANGE: -25°C~+70°C;
 - SALT SPRAY TEST: 8H(EXCLUDING RIVETED BENDS)

序号	名称	材料	表面	备注
3	外壳	SUS	镀镍	
2	端子	磷铜	焊料区镀锡, 接触区镀金(1u)	
1	基座	LCP	黑色	

Ordering Information

HC-RJ45 - *** * - * - * * * - 06

Series 1012 0106 0109	Connector Package 1012 0106 0109	Ports 1: 1个端口 2: 2个端口 3: 3个端口 4: 4个端口 6: 6个端口 7: 7个端口	LED/EMI Style 1: 带灯 2: 带灯 3: 带灯 4: 带灯 5: 带灯 6: 带灯 7: 带灯	LED Color 1: 蓝色 2: 蓝色 3: 蓝色 4: 蓝色 5: 蓝色 6: 蓝色 7: 蓝色	Type 1: 直插式 2: 直插式 3: 直插式 4: 直插式 5: 直插式 6: 直插式 7: 直插式	产品序号
--------------------------------	--	---	---	---	--	------

		GENERAL TOLERANCE		制图	深圳市华灿天禄电子有限公司 ShenzhenuacantianluELECTRONICS CO., LTD			
		DIM	TOL	审核				
		X.X	±0.30	批准	产品名称	网络插座 (沉板5.65 带灯无弹 DIP 16.2x9.9x15.4)	版本	A
		X.XX	±0.20	比例	产品料号	HC-RJ45-0109-1-2-1M03-06	REV.	
		X.XXX	±0.10	投影	材料		UNIT	mm
1	初版发行	日期	±3.0°	投影	材料		SHEET	1/1
序号	变更内容	日期						
No.	MODIFY CONTENT	MODIFY DATE						