



NOTES:

1.MATERIAL:

- 1.1 Housing:Thermoplastic plastics
- 1.2 Contact:Copper Alloy
Au plated on contact area
Tin plating on solder tail
Nickel under plating over all
- 1.3 Shell:Nickel plating on SUS

2.characteristics:

- 2.1 Rating Voltage : 125V AC RMS
 - 2.2 Rating Current:500 mA
 - 2.3 Contact Resistance:40 m Ω MAX.
 - 2.4 Insulation Resistance:100 M Ω MIN.
 - 2.5 Withstanding Voltage:AC 500V between adjacent contacts
 - 2.6 Mating force: 30N/3.0KG Max
 - 2.7 Life test:750Cycles MIN.
 - 2.8 Temperature Range: -40°C ~+85°C.
- The product must be compliance ROHS

序号	名称	材料	表面	备注
3	外壳	SUS	镀镍	
2	端子	磷铜	半金锡	
1	基座	LCP	黑色	

			GENERAL TOLERANCE	制图 DRAWING				
			DIM TOL	审核 CHECK				
			X.X ± 0.30	批准 APPROVAL	产品名称 TITLE	网络插座 (卧贴 无灯无弹 4脚插板 带柱)	版本 REV.	A
1	初版发行		X.XX ± 0.20	比例 SCALE	产品料号 PART NO.	HC-RJ45-044S-1-4-09	单位 UNITS	mm
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	X.XXX ± 0.10	投影 Projection	材料 MATERIAL		页次 SHEET	1/1
			Angle $\pm 3.0^\circ$					

 深圳市华灿天禄电子有限公司
ShenzhenhuacantianluELECTRONICS CO.,LTD