



MATERIAL:

HOUSING:PA66, PBT, BLACK.
 TERMINAL:PHOSPHOR BRONZE ∅0.46MM
 GOLD PLATING.

DURABILITY:750 CYCLES MIN, 12.5MM/MINUTE.
 INSERTION FORCE:2.2KG. F MAX.
 RETENTION STRENGTH:7.7KG. F BETWEEN JACK AND PLUG.
 OPERATING TEMPERATURE:-40℃~+85℃.
 STORAGE TEMPERATURE:-40℃~+85℃.
 ALL CRITICAL DIMENSIONS WITH “*” .

VOLTAGE:125 VOLTS AC.
 CURRENT RATING:1.5AMP.
 DIELECTRIC STRENGTH:1000 VAC RMS 50HZ OR 60HZ, 1MIN.
 INSULATION RESISTANCE:500MEGA OHMS MIN, INITIAL
 AFTER 500V DC FOR 1 MINUTE.
 CONTACT RESISTANCE:SINGLE TERMINAL 30 MILLIOHMS MAX.
 INITIAL 50 MILLIOHMS MAX.
 AFTER DURABILITY TEST.

			GENREL TOLERANCE	制图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
			DIM TOL	审核 CHECK				
			X.X ±0.30	批准 APPROVAL	产品名称 TITLE	网络插座 (无灯无弹 蓝全塑)	版本 REV.	A
			X.XX ±0.20	比例 SCALE	产品料号 PART NO.	HC-RJ45-55E-1-6-L	单位 UNITS	mm
			X.XXX ±0.10	投影 Projection	材料 MATERIAL		页次 SHEET	1/1
1	初版发行		Angle ±3.0°					
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE						