



NOTES:
 MATERIAL
 1.HOUSING MATERIAL: LCP BLACK UL94V-0
 2.CONTACT MATERIAL: C5191 R-H,T=0.30mm
 3.SHELL: BRASS R-H,T=0.2mm
 FINISH:
 1.CONTACT PLATING: 50u" MIN. NICKEL PLATED UNDER ALLOVER
 80u" MIN. TIN PLATED IN SOLDERING AREA
 GOLD PLATED IN CONTACT AREA
 2.SHELL PLATING: 30u" MIN NICKEL PLATED ALLOVER
 ELECTRICAL:
 1.VOLTAGE RATING: 125 VAC RMS
 2.CURRENT RATING: 15 AMP
 3.CONTACT RESISTANCE: 30 MILLIOHMS MAX
 4.INSULATION RESISTANCE: 500 MEGOHMS MIN @ 500V DC
 5.DIELECTRIC WITHSTANDING VOLTAGE : 500V AC R.M.S MIN
 MECHANICAL:
 1.DURRABILITY: 750 CYCLES MIN
 2.PCB RETENTION PRE-SOLDER: 1 LB MIN.

序号	名称	材料	表面	备注
3	外壳	黄铜	镀镍	
2	端子	C5191	焊料区镀锡， 接触区镀金(1u)	
1	基座	LCP	黑色	

Ordering Information

HC-RJ45 - *** * - * - * - * * * - 06

Series (系列号)	Connector Package (连接器封装)	Ports (端口)	LED/EMI Style (LED/EMI 样式)	LED Color (LED 颜色)	Type (型式)	Product No. (产品序号)
1012	DIP	1, 2	1, 2	1, 2	1, 2	1, 2
0106	S=SMT	3, 4, 5, 6, 7, 8	3, 4, 5, 6, 7, 8	3, 4, 5, 6, 7, 8	3, 4, 5, 6, 7, 8	3, 4, 5, 6, 7, 8
0108		9, 10, 11, 12	9, 10, 11, 12	9, 10, 11, 12	9, 10, 11, 12	9, 10, 11, 12

		GENERAL TOLERANCE		制图	
		DIM	TOL	DRAWING	
		X.X	±0.30	审核	
		X.XX	±0.20	CHECK	
		X.XXX	±0.10	批准	
1	初版发行	Angle	±3.0°	APPROVAL	
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE		投影 Projection	

深圳市华灿天禄电子有限公司
 ShenzhenhuacantianluELECTRONICS CO., LTD

产品名称 TITLE	网络插座 (沉板1.1 带灯无弹 DIP 16.18x9.9x14.6 带双耳)	版本 REV.	A
产品料号 PART NO.	HC-RJ45-1012-1-2-1M01-06	单位 UNITS	mm
材料 MATERIAL		页次 SHEET	1/1