



- NOTES:
- MATERIAL:
 - HOUSING: LCP ,COLOR IS BLACK;
 - CONTACT: PHOSPHOR COPPER ;
 - FINISH: GOLD PLATED G/Fu²;
 - ELECTRICAL:
 - VOLTAGE RATING: 125 VAC RMS;
 - CURRENT RATING: 1.5 AMP;
 - CONTACT RESISTANCE: 35MILLIOHMS MAX.;
 - WITHSTAND VOLTAGE: 500 VAC RMS 50(60)Hz,1MIN.;
 - INSULATION RESISTANCE: 500MEGOHMS MIN @500V DC.;
 - MECHANICAL:
 - MATING/UNMATING FORCE: 22N MAX.;
 - RETENTION STRENGTH: 50N MIN.;
 - OPERATING LIFE: 750 CYCLES MIN.;
 - ENVIRONMENTAL:
 - STORAGE TEMPERATURE RANGE: -40°C~+85°C;
 - OPERATION TEMPERATURE RANGE: -25°C~+70°C;
 - SALT SPRAY TEST:8H(EXCLUDING RIVETED BENDS)

序号	名称	材料	表面	备注
3	外壳	SUS	镀镍	
2	端子	磷铜	焊料区镀锡,接触区镀金(1u)	
1	基座	LCP	黑色	

Ordering Information

HC-RJ45 - *** * - * - * * * - 06

Series 1012 0109	Connector Package 1012 0106 S=SMT	Ports 1: 1 2: 2 3: 3 4: 4	LED/EMI Style 1: 1 2: 2 3: 3 4: 4	Color 1: 1 2: 2 3: 3 4: 4	Type 1: 1 2: 2 3: 3 4: 4	产品序号
------------------------	---	---------------------------------------	--	---------------------------------------	--------------------------------------	------

			GENERAL TOLERANCE	制图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM TOL	审核 CHECK	产品名称 TITLE	网络插座 (沉板4.2 无灯无弹 DIP 16.3x11.1x15.2)	版本 REV.	A
			X.X ±0.30	批准 APPROVAL	产品料号 PART NO.	HC-RJ45-0109-1-4-1M02-06	单位 UNITS	mm
			X.XX ±0.20	比例 SCALE	材料 MATERIAL		页次 SHEET	1/1
			X.XXX ±0.10	投影 Projection				
1	初版发行		Angle ±3.0°					
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE						