



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

TYPE 1



TYPE 2



SPECIFICATIONS

Rated Current:0.75AMP

Contact Resistance:30mΩ Max

Withstand Voltage:500V AC/DC

Insulation Resistance:1000MΩ Min

Operation Temperature:-40°C to +105°C

Contact Material:Brass

Contact Plating:Au Over Ni

Insulator Material:Polyester(UL94V-0)

Standard: PA6T

Max.Processing Temp: 260°C±5°C 5S

Dimension antitheses list

ITEM	PA	PC	C	W	L
Standard	2.00	1.40	3.70	3.60	6.10
Alternate					

Ordering Information

PZ 100	- *	- N	- Z	- C*	- **	- *	- *
No. of Rows 1=Single Row 2=Dual Row	No. of Pins 02-40Pin (02=02Pin) (40=40Pin)	Type (02=02Pin) (40=40Pin)	Length (mm) (02=02Pin) (40=40Pin)	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold	Double Plastic (02=02Pin) (40=40Pin)	1=TYPE 1 2=TYPE 2	

			GENERAL TOLERANCE		制 图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM	TOL	审 核 CHECK		产品名称 TITLE	1.00 单排 排针 双塑 贴片	版 本 REV.	A
			X. X	±0.30	批 准 APPROVAL		产品料号 PART NO.	PZ100-1-N-S-C3.7-XX-DP-X(L6.1)	单 位 UNITS	mm
			X. XX	±0.20	比 例 SCALE		材料 MATERIAL		页 次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	X. XXX	±0.10	投 影 Projection					
			Angle	±3.0°						