

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)

SPECIFICATIONS

Rated Current:1.5AMP
Contact Resistance:20m Ω Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000M Ω Min
Operation Temperature:-40°C to +105°C

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V-0)
Standard: PA6T
Max.Processing Temp: 230°C for 30-60 seconds
(260°C for 5 seconds)

Dimension antitheses list			
ITEM	PA	PC	L
Standard	4.00	2.80	8.80
Alternate			

Ordering Information

PZ 200 - * - N - WS - * - **

No.of Rows 1=Single Row 2=Dual Row	No.of Pins 2-40Pin	Type 2=直针 N=带针 S=空针 WS=带插	Length (mm)	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin
--	-----------------------	---------------------------------------	----------------	--

			GENERAL TOLERANCE		制 图	 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
			DIM	TOL	DRAWING				
					审 核				
			X. X	± 0.30	批 准				
			X. XX	± 0.20	APPROVAL				
1	初版发行		X. XXX	± 0.10	比 例	产品名称	2.00单排 排针 卧贴(塑高2.0)	版本	A
序号	变更内容	日期	Angle	$\pm 3.0^\circ$	SCALE	PART NO.	PZ200-1-N-WS-2.0-XX(L8.8)	单 位	mm
No.	MODIFY CONTENT	MODIFY DATE	投影		Projection	材料		页 次	1/1
						MATERIAL		SHEET	