



Operating voltage : 60 AC/DC

PM 200	- *	- N	- W	- *	- **	- C	
No. of Rows 1=Single Row 2=Dual Row		No. of 01-40Pin	Type 0101 0102 01-10/02	Length	Contact 20-Gold	Plating Flash	Round Pin
					C111u* Gold		
					C211u* Gold		
					C35u* Gold		
					G410u* Gold		
					G615u* Gold		
					G630u* Gold		
					S0:Gold Flash/Tin		
					S1:Tin		

			GENERAL TOLERANCE		制 图 DRAWING		 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD					
			DIM	TOL	审 核 CHECK							
			1	初版发行	X.X	±0.30	批 准 APPROVAL		产品名称 TITLE	2.0 单排 圆针 弯排母 型高2.8	版 本 REV.	A
			序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	X.XX	±0.20	比 例 SCALE		产品料号 PART NO.	PM200-1-N-W-2.8-XX-C	单 位 UNITS
			X.XXX	±0.10	投 影 Projection		材 料 MATERIAL		页 次 SHEET	1/1		
			Angle	±3.0°								