



Soldering temperature: $260^{\circ}\text{C} \pm 5^{\circ}$ 5S

PM	200	-	*	-	N	-	Z	-	*	-	**	-	C		
	No. of Rows 1=Single Row 2=Dual Row				No. of Pins 02-40Pin		Type Z=直插 S=贴片 WS=带贴		Length (mm)		Contact G0:Gold G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin		Plating Flash Gold Gold Gold Gold Gold Gold Flash/Tin		Round Pin (mm)

			GENERAL TOLERANCE	制 图 DRAWING	 深圳市华灿天禄电子有限公司 ShenzhenhuacantianlueELECTRONICS CO.,LTD			
			DIM TOL	审 核 CHECK				
			X.X ±0.30	批 准 APPROVAL	产品名称 TITLE	2.0 单排 排母 圆直针	版 本 REV.	A
1	初版发行		X.XX ±0.20	比 例 SCALE	产品料号 PART NO.	PM200-1-N-Z-3.0-XX-C	单 位 UNITS	mm
			X.XXX ±0.10					
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle ±3.0°	投 影 Projection	材 料 MATERIAL		页 次 SHEET	1/1